





PART NO.: 106344 ezEX™44 RJ45 connector

EIGHT CONDUCTOR MODULAR PLUG
 FOR CONDUCTORS WITH AN O.D. RANGE OF .039" - .044" (0.99—1.12mm)
 MAX CABLE JACKET OD: .290" (7.37MM)
 USES .012 CONTACT
 FOR SOLID OR STRANDED WIRE APPLICATIONS
 24—22 AWG
 RoHS2 & UL COMPLIANT
 MADE IN USA



SPECIFICATIONS:

PERFORMANCE:	MEETS OR EXCEEDS CATEGORY 6 ANSI/EIA 568-C.2 PERFORMANCE TUNED TO CABLES MEETING CATEGORY 6 SPECIFICATIONS
TRANSMISSION:	RATED UP TO 10 GIGABIT
CONTACT MATERIAL	PHOSPHOR BRONZE—.012 THK
CONTACT PLATING	50 MICRO INCH SELECTIVE 24 CARAT HARD GOLD IN CONTACT AREA OVER 100 MICRO INCH MINIMUM NICKEL PLATE.
PLUG MATERIAL	POLYCARBONATE
PLUG TOLERANCES/DIMS	COMPLIES WITH F.C.C. REQUIREMENTS
OPERATION TEMPERATURE	-40° TO +85° C
FLAME AUTO EXTINGUISH	94-VO
INSERTION/EXTRACTION	1000 CYCLES
CONTACT RESISTANCE	10 MILLIOHMS MAX.
CURRENT VOLTAGE	30 VAC/42 VDC AT 1.5 AMPS