

CAT6A UTP SLIMLINE PATCH LEADS

500MHZ COMPONENT TESTED

The Slimline Cat6A UTP patch leads conform to the ANSI/TIA-568.2 specification. Patch leads are wired to the T568A pin-out specification.

They are component level tested and are made with tangle free slimline injection moulded boots and latch down plugs in various colours and lengths.





FEATURES:

- Produced by an ISO9001 and ISO14001 certified manufacturer
- 100% tested, UL Recognized
- High flexible bend radius
- Available in 8 colours
- Covered by lifetime warranty

SPECIFICATIONS:

- Perfect for cabling network data cabinets
- Perfect for cabling home structured wiring boxes
- Perfect for cabling high density patch environment
- **Not compatible with HDBaseT connectivity**

T568A Cabling Pinout Specifications



PRODUCT CODES

LENGTH	BEIGE	BLACK	BLUE	GREEN	GREY	RED	YELLOW	WHITE
0.25m	PLS-C6-0.25	PLSK-C6-0.25	PLSE-C6-0.25	PLSG-C6-0.25	PLSGY-C6-0.25	PLSR-C6-0.25	PLSY-C6-0.25	PLSW-C6-0.25
0.5m	PLS-C6-0.5	PLSK-C6-0.5	PLSE-C6-0.5	PLSG-C6-0.5	PLSGY-C6-0.5	PLSR-C6-0.5	PLSY-C6-0.5	PLSW-C6-0.5
0.75m	PLS-C6-0.75	PLSK-C6-0.75	PLSE-C6-0.75	PLSG-C6-0.75	PLSGY-C6-0.75	PLSR-C6-0.75	PLSY-C6-0.75	PLSW-C6-0.75
1m	PLS-C6-1	PLSK-C6-1	PLSE-C6-1	PLSG-C6-1	PLSGY-C6-1	PLSR-C6-1	PLSY-C6-1	PLSW-C6-1
1.25m	PLS-C6-1.25	PLSK-C6-1.25	PLSE-C6-1.25	PLSG-C6-1.25	PLSGY-C6-1.25	PLSR-C6-1.25	PLSY-C6-1.25	PLSW-C6-1.25
1.5m	PLS-C6-1.5	PLSK-C6-1.5	PLSE-C6-1.5	PLSG-C6-1.5	PLSGY-C6-1.5	PLSR-C6-1.5	PLSY-C6-1.5	PLSW-C6-1.5
2m	PLS-C6-2	PLSK-C6-2	PLSE-C6-2	PLSG-C6-2	PLSGY-C6-2	PLSR-C6-2	PLSY-C6-2	PLSW-C6-2
2.5m	PLS-C6-2.5	PLSK-C6-2.5	PLSE-C6-2.5	PLSG-C6-2.5	PLSGY-C6-2.5	PLSR-C6-2.5	PLSY-C6-2.5	PLSW-C6-2.5
3m	PLS-C6-3	PLSK-C6-3	PLSE-C6-3	PLSG-C6-3	PLSGY-C6-3	PLSR-C6-3	PLSY-C6-3	PLSW-C6-3