

PRODUCT SPECIFICATION

FEATURES:

Current Meter: True RMS Current Meter, Voltage, Frequency, Power Factor, Active Power, Apparent Power, Total kWh, Sub-total kWh.
Power Monitor: Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols: Http, Https, SNMP, DHCP, UDP
Outlet Control: Individual, Group, Schedule, Auto Ping
Power Delay: Power On/Off Sequence can be Defined
Alarm Thresholds: User-Defined Alarm Thresholds for Warning and Overload
Event Alert: Email, Trap, Audible Alarm

GENERAL:

Output: (8) IEC 320 C13
Input: (1) IEC320 C20 Inlet; IEC320 C19 to C20 Power Cord 3M
Protection: (1) 16 AMP Circuit Breaker



COMMUNICATION:

SSL Indication: (1) Yellow LED
DHCP Indication: (1) Green LED
Output Status: (8) Green LED
Circuit Status: (1) Red LED
Network: (1) RJ45 for Ethernet
Temp./Humidity: (1) RJ11 for ENV probe connection
PDU ID: 1 Digits Seven Segments for PDU Identification
Meter: 3 Digits Seven Segments

OPERATION:

Nominal Voltage: 230V
Voltage: 200V~ 240V full range
Frequency: 50/60HZ full range
Max. Output Current: 16 Amp
Temperature: 0 ~ 40 Celsius degree
Humidity: 0% ~ 90%
Size: 125 x 432 x 44 mm
Weight: 3.5 kg

REGULATORY APPROVALS:

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
FCC Part 15 Class A, ICES-003

