

APC Smart-UPS C 2000VA LCD RM 2U 230V SMC2000I-2U



- Includes: CD with software, Documentation CD, Installation guide, Rack mounting brackets, USB cable


Output

Output power capacity	1.3kWatts / 2.0kVA
Max Configurable Power (Watts)	1.3kWatts / 2.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50 Hz Sync to mains
Topology	Line interactive
Waveform type	Sine wave
Output Connections	(6) IEC 320 C13 (2) IEC Jumpers
Transfer Time	8 ms typical : 10 ms maximum

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	IEC 320 C20
Input voltage range for main operations	180 - 287V
Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	APCRBC133 

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS C 2000VA LCD RM 2U 230V | SMC2000I-2U | Downloaded on 01/18/2021 (EST)

Batteries & Runtime	
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	144 Watts
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering	
Surge energy rating	300Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	89MM, 8.9CM
Maximum Width	480MM, 48.0CM
Maximum Depth	470MM, 47.0CM
Rack Height	2U
Net Weight	26.2KG
Shipping weight	30.16KG
Shipping Height	250MM, 25.0CM
Shipping Width	590MM, 59.0CM
Shipping Depth	600MM, 60.0CM
Color	Black
Units per Pallet	16.0

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS C 2000VA LCD RM 2U 230V | SMC2000I-2U | Downloaded on 01/18/2021 (EST)

Environmental	
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	42.0dBA
Online thermal dissipation	81.0BTU/hr

Conformance	
Approvals	C-Tick, CE, EAC, GOST, GS Mark, IRAM, SABS, VDE
Equipment protection policy	Lifetime : \$150000
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.