C3X Al-Powered Dark-fighter Camera

Security Video For Smart Life

2019.11



EZVIZ



01 02

Introduction Features



03 04

Operation

SPEC

Introduction









Appearance





Dimensions





Shuttle Weight: 425g

Box Contents



- ullet
- Power adapter is not included with the PoE camera model \bullet





Power Adapter



Quick Start Guide

The camera appearance is subject to the actual model you have purchased



Features



CBX

AI-Powered Dark-Fighter

Dual-lens Wi-Fi camera with built-in Al.

Meet the world's first commercial-grade security camera with a dual-lens setup. Night time color video has become a reality, even with the absence of supplemental lights. And built-in AI algorithms just made everything easier. Now you can get accurate alerts when people and vehicles appear in your specified zones. Get protection with the C3X, in high-tech and professional fashion.



Intelligent Dual-Lens



Color Night Vision



Embedded Al Deep Learning Algorithm



Human/Vehicle Shape Detection



Active Defense with Siren and Strobe Light



H.265

Dustproof and Waterproof IP67

H.265 Video

Compression



Customizable Voice Alerts



The first dual-lens seen on a security camera.

In the dual-2 MP camera setup, vivid color imaging is accomplished using two lenses – one lens records the ambient brightness and the other captures color information. Then the two images are merged using EZVIZ's own proprietary algorithm to create an image that is rich in details and realistic color.





Revolutionary color night vision without spotlights.

Leveraging supplemental lights to achieve color night vision was brilliant – until the introduction of the C3X. The C3X uses dual lenses and dual infrared lights to render better color images even in the lowest light conditions. There's no need for spotlights. C3X's colors are more natural, and the image is more evenly-illuminated.



C3X Night Vision*

*In extreme environments, such as a completely enclosed warehouse or rural areas in a moonless cloudy night, the C3X will shift to black/white mode to ensure utmost image clarity.



Night Vision with Built-in LEDs

Traditional Black/White Vision







Motion-triggered recording of people and vehicles.

for you.





With a built-in deep learning model, the C3X can detect the motion of person and vehicle shapes in real-time. Now you can receive the precise motion alerts you've always wanted. When no one is watching, the C3X takes the shift



Actively protects places that matter.

The C3X lets you draw particular zones on the EZVIZ App to protect what matters to you the most. You can decide whether you want to keep people, cars, or both out of the zones. Upon detection of objects of interest, the camera will issue a loud siren and flash the strobe light to drive intruders away. You'll receive a notification in a split second.





Customize your voice alerts.





The C3X lets you record your own voice for customized greeting or deterrence. For example, when visitors park cars in prohibited areas, the camera will play a pre-recorded message and instruct the drivers to park elsewhere

Save money on storage and bandwidth.

Using the latest H.265 video compression technology, the C3X renders clearer and smoother video while reducing the need for data storage space and bandwidth







Designed to brave all types of weather.

snowy days, giving you year-round peace of mind.





With a whole metallic enclosure and an IP67 rating, the camera can withstand rainy, sunny, stormy, and even

Operation

03





Setup For Wi-Fi Camera

Step 1 Power-on

Connect the camera to power outlet with the power adapter, as shown below.



- Hold the RESET button for 5 seconds when adding cameras or Wi-Fi connection failed.
- Please make sure your phone is connected to the 2.4GHz Wi-Fi from the router for Wi-Fi configuration.

Step 2 Camera Setup

1. Create a user account

- Connect your mobile phone to Wi-Fi.

- Download and install the EZVIZ app by searching "EZVIZ" in App Store or Google Play.

- Launch the app and register an EZVIZ user account following the start-up wizard.

2. Add a camera to EZVIZ

- Log in the EZVIZ app.

- From the EZVIZ app Home screen, tap "+" on the upper-right hand corner to go to the scan QR code interface.

- Scan the QR code on the body of the camera, follow the EZVIZ app wizard to finish Wi-Fi configuration





















Setup For PoE Camera

Step 1 Power-on

Option 1. Connect your PoE camera to a PoE Switch/NVR.

- Connect the Ethernet cable to the PoE port of your camera.

- Connect the other end of the Ethernet cable to the PoE port of your PoE switch or NVR.

- Connect the LAN port of your PoE Switch or NVR to the LAN port of a router via the Ethernet cable.





Option 2. Connect your PoE camera to a router

- Connect the power adapter cable (sold separately) to the camera's power port.
- Plug the power adapter into an electrical outlet.
- Connect the Ethernet cable to the PoE port of your camera.
- Connect the other end of the Ethernet cable to the LAN port
- of a router.







Setup For PoE Camera

Step 2 Camera Setup

- **1.** Create a user account
- Connect your mobile phone to Wi-Fi.
- Download and install the EZVIZ app by searching "EZVIZ" in App Store or Google Play. - Launch the app and register an EZVIZ user account following the start-up wizard.

2. Add a camera to EZVIZ

- Connect the camera to the LAN port of your router with the Ethernet cable.
- Log in the EZVIZ app.
- From the EZVIZ app Home screen, tap "+" on the upper-right hand corner to go to the scan QR code interface.

- Scan the QR code on the body of the camera, follow the EZVIZ app wizard to finish Wi-Fi configuration







Camera Installation

You can install the camera on the wall or ceiling.

- Make sure the wall is strong enough to withstand three times the weight of the camera.
- Recommended installation height: 3m (10 inch).
- Avoid positioning the camera in an area that gets a lot of light shining directly into the camera lens.

3.1 Install the Camera

- Place drill template onto the surface you have chosen to mount the camera.

- (For the cement wall/ceiling only) Drill screw holes according to the template, and insert three anchors. - Use three metal screws to fix the camera base according to the template.





2 Adjust the Surveillance Angle

- Loosen the adjusting screw.
 - Adjust the surveillance angle as your desired place.
- Tighten the adjusting screw when you have your camera in the position you want.



Install the SD Card

1. Remove the cover on the camera.

- 2. Insert the Micro SD card (sold separately) into the card slot as shown in the figure below.
- 3. Place the cover back on.
- 5. In the EZVIZ app, tap the Storage Status in the Device Settings interface to check the SD card status.

6. If the memory card status displays as Uninitialized, tap to initialize it.







AP Pairing

() Make sure your EZVIZ app is V3.6 or above.





Alarm Setting

■■■中国移动	२ 15:07	🕒 🎱 100% 🗩
<	Setting	S
E Res / / e	C3X(D67905115) D67905115	>
Audio		
When disa will not hav	bled, both live view ve audio.	and recorded videos
Status Lig	ght	
Alarm No	otification	Enable >
Alarm No Time Zon	otification	Enable > UTC+03:00 >
Alarm No Time Zon Date Forr	otification ne mat	Enable > UTC+03:00 > DD-MM-YYYY >
Alarm No Time Zon Date Forr Wi-Fi	otification ne mat	Enable > UTC+03:00 > DD-MM-YYYY > zouzou <section-header></section-header>
Alarm No Time Zon Date Forr Wi-Fi Storage S	otification ne mat Status	Enable > UTC+03:00 > DD-MM-YYYY > zouzou >

•Ⅱ 中国移动 夺	15:07
<	Alarm Notifica
Alarm Notific	ation
You will receive with no Notifica	e notifications 24/7 ation Schedule set.
Notification S	Schedule
Set Notificati	ion Schedule
When enabled, notification on/ settings.	the device will turn off according to yo
Motion Deteo	ction Area
Motion Deteo	ction Sensitivity
Select the m	ode
An audible war	ning and alarm not





Enable Notification Schedule, the device will turn the message push notification on/off according to the scheduled settings.

We can draw motion detection area for alarm only.

- (3) 0: Motion detection off
 - Low sensitivity. Movement over wide areas will trigger motion alerts
 High sensitivity. Movement over small areas
 - will trigger motion alerts



(1)

Intensive, Soft, Mute or Custom Sound ON/OFF Light flashing reminder.

]

1

IS

Storage Setting

< Settings	Storage Status
IR Light	
When disabled, image quality may be impacted in the dark.	Memory Card Not Initialized
Alarm Notification Disable >	
Time Zone UTC+08:00 >	
Date Format MM-DD-YYYY >	
Wi-Fi zouzou 🎅 >	
storage Status	
Device Version V5.2.8 build 190604 No new version available.	
Image Encryption	
Change Encryption Pas >	
The default password is the device verification code.	
Flip Image	

Step1: Find the "Storage Status" in the main setting page Step2: Check the status of the memory card



			_			
<	Memory Card			<	Storage Status	
Memory Caro	ł	Initialize				
Not Initialized					Memory Card	>
initialize the storage ormally.	e medium before it ca	n save			in use. Only record for detivities.	
				All Day		\bigcirc
~2.	Initialized +	ho	·	Stop	1. Managa tha	card
	J. IIIIIaIIZEU L			JUCH	4. IVIALIASE LIE	Laiu

and change the recording

strategy if needed

Step3: Initialized the memory card if it's first used

Comparison

	C3W (ezGuard)	C3W (Color night vision)	C3WN	C3X
Appearance				
Resolution	HD, Full HD	Full HD	Full HD	Full HD
Video coding standard	H.264	H.264, H.265	H.264	H.264, H.265
User defined alarm tones	Not support	Supports	Not support	Supports
Active Light and Sound alarm	Supports	Supports	Not support	Supports
IP Grade	IP 66	<i>IP 67</i>	IP 66	<i>IP 67</i>
Color night image	Not support	Supports	Not support	Supports
Two-Way talk	Supports	Supports	Not support	Supports
Max. SD card	256G	256G	256G	256G
Human/car Shape Detection	Not support	Not support	Not Support	Supports
AI Deep Learning	Not equipped	Not equipped	Not equipped	Equipped











Camera

Image Sensor	1/2.7" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	2.8 mm @ F1.6, view angle: 105° (Horizontal), 120° (Diagonal)
Min. Illumination	color night vision, 0.0005 lux
Lens Mount	M8
DNR	3D DNR
WDR	Digital WDR

Compression

Video Compression	H.264 / H.265
Video Bit Rate	Ultra-HD; HD; Standard. Adaptive bit rate.

Image

ſ	Max. Resolution	1920 × 1080
	Frame Rate	50Hz: 25fps; Self-Adaptive during network transmission
	BLC	Supports
V		

Network

C		
	Smart Alarm	Motion detection, human shape detection, vehicle shape detection
	Setup Motion Detection Area	Supports
	Wi-Fi Pairing	AP paring

Protocol Interface Protocol	EZVIZ cloud proprietary protocol EZVIZ cloud proprietary protocol
Interface	
Storage	Micro SD card slot (Max. 256 GB)
Wired Network	RJ45 X 1 (10M/100M self-adaptive Ethernet port)
Wi-Fi	
Standard	IEEE802.11b/g/n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20 MHz
Security	64 / 128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK
Transmission Rate	11b: 11 Mbps, 11g: 54 Mbps, 11n: 144 Mbps
General	
Operating Conditions	-30°C to 60°C (-22°F to 140°F), humidity 95% or less (non-condensing)
Power Supply	DC 12V±10%
Power Consumption	Max. 12W
IR Range	Max. 30 meters (98.43 feet)
IP Grade	IP67
Dimensions	72 x 72 x 150 mm (2.83 x 2.83 x 5.9 inch)
Packaging Dimensions	253.5 x 111.5 x 93.5 mm (9.98 x 4.39 x 3.68 inch)
Weight	425g (0.94 lb)

e



Thank You

For more information, visit https://www.ezvizlife.com/ Join the EZVIZ communities on Facebook, Instagram, Twitter and YouTube (@ezviz_global)



