

CAT6 COMPONENT LEVEL UTP PATCH PANEL

FEATURES:

- CAT6 patch panel exceeds ANSI/TIA-568-C.2 CAT6 and ISO 11801 2nd edition Class E and EN50173-1 standards
- Component level tested & certified
- Backward compatible to CAT5e, 5 and 3
- Supports termination wiring (T568A/B)
- Including rear cable support bar
- Including plastic labeling kit
- Colour Black



PRODUCT CODES

Model Code	TYPE	PORTS
PP-C6-24LCSB	Dual Type IDC	24 (With Cable Support Bar)

PRODUCT SPECIFICATIONS

Material	1.6mm Steel plate
Colour	Black
Installation	19 inch frame/cabinet
Jack wiring	8p 100 micron inch Gold plated over 100 micron inch nickel
Retention strength	7.7kg between jack and plug
Insertion force	20N max
Operating temperature	-10°C ~ 60°C
Plug insertion life	750 cycles min.
IDC insertion life	200 cycles min.
Conductor	22-26 AWG
Compliance Standards	UL, ETL and 3P certified, ANSI/TIA-568-C.2, ISO/IEC 11801 CAT6 with the applicable electrical transmission characteristics. ETL verified to ANSI/TIA-568-C.2 and ISO /IEC 11801 CAT6 and teh product model(s) and or brand name.



Intertek