

APC Smart-UPS X 1500VA Rack/Tower LCD 230V with Network Card

SMX1500RMI2UNC

Call for More Information 800-800-4272



- Includes: CD with software, Documentation CD, Installation guide, Rack mounting support rails, Removable support feet, Smart UPS signalling RS-232 cable, USB cable

| Output | |
|----------------------------------|------------------------------------|
| Output power capacity | 1.2kWatts / 1.5kVA |
| Max Configurable Power (Watts) | 1.2kWatts / 1.5kVA |
| Nominal Output Voltage | 230V |
| Output Voltage Distortion | Less than 5 % |
| Output Frequency (sync to mains) | 50/60 Hz +/- 3 Hz Sync to mains |
| Topology | Line interactive |
| Waveform type | Sine wave |
| Output Connections | (8) IEC 320 C13 (2) IEC Jumpers |

| Input | |
|---|----------------------------------|
| Nominal Input Voltage | 230V |
| Input frequency | 50/60 Hz +/- 3 Hz Auto-sensing |
| Input Connections | IEC 320 C14 |
| Cord Length | 6ft (1.8meters) |
| Input voltage range for main operations | 151 - 302 Adjustable, 160 - 286V |
| Number of Power Cords | 1 |

| Batteries & Runtime | |
|-----------------------|---|
| Battery type | Lead-acid battery |
| Typical recharge time | 3hour(s) |
| Replacement Battery | APCRBC115  |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

| Batteries & Runtime | |
|-------------------------------|--|
| Expected Battery Life (years) | 3 - 5 |
| RBC Quantity | 1 |
| Battery Charge Power (Watts) | 103 Watts |
| Extended Run Options | APC-Smart-UPS-X-1500VA-Rack-Tower-LCD-230V-with-Network-Card (Available in Technical Tab on site) |
| Runtime | View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site) |
| Efficiency | View Efficiency Graph (Available in Technical Tab on site) |

| Communications & Management | |
|--------------------------------|--|
| Interface Port(s) | SmartSlot, USB |
| Pre-Installed SmartSlot™ Cards | AP9631 (Available in Technical Tab on site) |
| Control panel | Multifunction LCD status and control console |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| Emergency Power Off (EPO) | Yes |

| Surge Protection and Filtering | |
|--------------------------------|--|
| Surge energy rating | 645Joules |
| Filtering | Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449 |

| Physical | |
|-----------------|-----------------------------|
| Maximum Height | 3.5inches (89MM, 8.9CM) |
| Maximum Width | 17.01inches (432MM, 43.2CM) |
| Maximum Depth | 19.29inches (490MM, 49.0CM) |
| Rack Height | 2U |
| Net Weight | 54.72lbs. (24.82KG) |
| Shipping weight | 66.14lbs. (30.0KG) |
| Shipping Height | 9.69inches (246MM, 24.6CM) |
| Shipping Width | 23.19inches (589MM, 58.9CM) |
| Shipping Depth | 24.41inches (620MM, 62.0CM) |
| Color | Black |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

| Physical | |
|------------------|-----|
| Units per Pallet | 8.0 |

| Environmental | |
|---|-------------------------------|
| Operating Temperature | 32 - 113 °F (0 - 45 °C) |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0 - 10000ft (0 - 3048meters) |
| Storage Temperature | -15 - 45 °C |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0 - 50000ft (0 - 15240meters) |
| Audible noise at 1 meter from surface of unit | 40.0dBA |
| Online thermal dissipation | 133.0BTU/hr |

| Conformance | |
|-------------------|---|
| Approvals | C-Tick, CE, EAC, EN 50091-1, EN 50091-2, VDE |
| Standard warranty | 3 years repair or replace (excluding battery) and 2 years for battery |

| Sustainable Offer Status | |
|--------------------------|--------------------------------|
| RoHS | Compliant |
| PEP | Available in Documentation tab |
| EOLI | Available in Documentation tab |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.