

APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack

SRT192RMBP



• Includes: Installation guide, Warranty card

| Output | |
|------------------------|-------|
| Battery Output Voltage | 192 V |

| Batteries & Runtime | |
|-------------------------------|---------------------------|
| Battery type | Lead-acid battery |
| Battery mounting | Stand alone battery stack |
| Expected Battery Life (years) | 3 - 5 |
| RBC Quantity | 2 |

| Physical | |
|------------------|-----------------|
| Maximum Height | 130MM, 13.0CM |
| Maximum Width | 432MM, 43.2CM |
| Maximum Depth | 683MM, 68.27CM |
| Rack Height | 3U |
| Net Weight | 91.0KG |
| Shipping weight | 105.5KG |
| Shipping Height | 420MM, 42.0CM |
| Shipping Width | 600MM, 60.0CM |
| Shipping Depth | 1000MM, 100.0CM |
| Color | Black |
| Units per Pallet | 1.0 |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications





APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack | SRT192RMBP | Downloaded on 01/28/2021 (EST)

| Environmental | |
|-----------------------------|---------------------------|
| Operating Temperature | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 (Non-condensing) % |
| Operating Elevation | 0 - 3048meters |
| Storage Temperature | -15 - 45 °C |
| Storage Relative Humidity | 0 - 95 (Non-condensing) % |
| Storage Elevation | 0 - 15240meters |

| Conformance | |
|-------------------|---------------------------|
| Approvals | OSHPD |
| Standard warranty | 2 years repair or replace |

| Sustainable Offer Status | |
|--------------------------|--------------------------------|
| RoHS | Compliant |
| Proposition 65 Warning | Available in Documentation tab |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.