



APC Easy UPS 1 Phase Online

Family Brochure

For IT professionals in small to medium businesses, Easy UPS Online provides basic power protection in unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.

APC Easy UPS Online is a versatile, high-quality, cost competitive UPS developed to handle a wide voltage range and inconsistent power conditions, delivering the quality millions of IT professionals around the world trust.

That's Certainty in a Connected World.



www.apc.com

Life Is 

APC[®]
by Schneider Electric

APC Easy UPS 1 Ph Online Features

- Tower Models (standard & extended runtime)
 - Available in 1, 2, 3, 6, 10 KVA
- Rack Models (standard & extended runtime)
 - Available in 1, 2, 3, 6, 10 KVA



Extended Runtime Models Available

Add external battery packs to scale runtime from minutes to hours, fulfilling the needs of long runtime applications

ECO Mode / Green Mode

Energy saving mode allows input voltage regulation range to be set/modified through the LCD display

Generator Compatible

Ensures clean, uninterrupted power to the loads during an extended power outage

High Power Factor

More real output power in watts: 0.8 PF for 1, 2 & 3 kVA, unity PF for 6 & 10 kVA

Environmentally Robust

Conformal coated

Intelligent Battery Management

Maximizes battery performance through intelligent precision temperature compensated charging

Overvoltage Cutoff Device Protection

Under special application with high voltage condition, OVCD protection will prevent the damage of UPS components and extend UPS lifespan

Input Power Factor Correction

Minimizes installation costs by enabling the use of smaller generators and cabling

Excellent Power Quality and Performance

True Double Conversion provides tight voltage, frequency regulation and zero transfer time for reactive loads

Wide Input Voltage Range

60% Load: 110-300VAC
(applicable to 6 & 10 kVA models)
Allows for unstable power environments and minimizes transfer to battery

USB Port / Serial Port

Provides management of the UPS via USB/serial communication

Flash Upgradeable Firmware

Allows for field updates of firmware via communication ports

LCD/LED Display

Intuitive interface provides detailed and accurate information about UPS status with ability to configure locally

Power Conditioning

Protects connected loads from surges, spikes, lightning and other power disturbances

Life Is On

APC[®]
by Schneider Electric

APC Easy UPS 1 Ph Online Additional Features

Built-in Automatic Bypass

Ensures seamless power to the load even in the event of catastrophic UPS failure

Emergency Power Off (EPO)

Immediately remove power to all connected equipment in the event of emergency (applicable to standard & extended runtime 6 & 10 kVA models)

Safety Agency Approved

Tested and approved to work with the connected service provider equipment and within the specified environment



Life Is On

APC[®]
by Schneider Electric


Easy UPS Online LCD Display





LCD Display


- 1 On/Off Status LED: indicates power is ON
- 2 On/Off Button: Press to turn UPS On or OFF
- 3 Alert LED: lashes red when UPS has a notification or is steady state when there is a fault
- 4 Mute/ESC button: Mutes alarm and serves as the Escape key when in the sub menus of the display
- 5 Enter Key: Press to enter the display menus and choose an option within the menu
- 6 Up/Down Arrows: Navigate keys through the display menus


LCD Display Icons


 UPS is on utility power
ON LINE

 UPS is on battery
ON BATT

 UPS is in bypass mode
BYPASS

 Replace battery
ON BATT

 An internal fault is detected
ALARM


 Overload- connected load is drawing more than the power rating


 Battery charge
LOW

 Load level
LOAD SENSITIVITY

 Mute: audible alarm disabled

EVENT LOG Event: illuminated when the user is reviewing the event log

 **SEE MANUAL** Alert: UPS has detected error. Please see user's manual for details

 ECO mode: illuminated when the unit provides utility power and power is within configured ranges

Life Is On

APC[®]
by Schneider Electric

Easy UPS Online Accessories

Additional solution enhancement options

Dry Contact Card (VGL9901I)

The UPS management accessory provides one dry contact input and six relay output interfaces to Easy UPS SRV series.

Ideal applications:

- IBM server, personal PC and workstation equipment
- Auto-controlled industrial equipment and communication applications



UPS Dry Contact Card
VGL9901I

SNMP Card (APV9601)

SNMP Card provides direct communication with your APC Easy UPS and monitors the following:

- UPS status: load, battery charge, voltage
- Battery status: healthy, capacity & runtime
- Shutdown Wizard: remotely shuts down and reboots server



UPS Network Management Card: APV9601



Rail Kits (SRVVK1, SRVVK2)

APC Easy UPS Rail Kit provides simple rack mount installation, allowing for easy UPS maintenance while minimizing space needed.

SRVVK1:

- Rail Kit for UPS / Battery Pack (700mm)

SRVVK2

- Rail Kit for Battery Pack (900mm)



SRVVK1



SRVVK2

Life Is On

APC[®]
by Schneider Electric

Technical Specifications

Easy UPS 1 Ph Online Standard Models (Tower)

Model		SRV1KI	SRV2KI	SRV3KI	SRV6KI	SRV10KI	
Input	Nominal Input Voltage	230Vac					
	Input Connection	IEC C14		IEC C20	Terminal Block		
	Input Frequency	50/60 Hz					
	Input Voltage Range (60% Load)	110 Vac – 285 Vac			110 Vac – 300 Vac ± 3%		
	Input Power Factor (100% Load)	≥ 0.95			≥ 0.99		
Output	Topology	Online					
	Output Power Capacity (Watts)	800 W	1600 W	2400 W	6000 W	10000 W	
	Output Power Capacity (VA)	1000 VA	2000 VA	3000 VA	6000 VA	10000 VA	
	Output Voltage	220/230/240VAC					
	Frequency (Battery Mode)	50/60Hz +/- 0.5%			50/60Hz +/- 0.1 Hz		
	Waveform Type	Pure Sinewave					
	Output Voltage Regulation	± 1%					
	Transfer Time (AC to DC)	Zero					
	Total Output Connections	IEC 3*C13	IEC 4*C13	IEC 6*C13+1*C19	Terminal Block		
	Efficiency (AC Mode)	88%			94%		
	Current Crest Ratio	3:1					
Battery	Battery Type	12 V / 9 AH X 2	12 V / 9 AH X 4	12 V / 9 AH X 6	12 V / 7 AH x 16	12 V / 9 AH x 16	
	Typical Recharge Time	4 hours recover to 90% capacity			3 hours recover to 90% capacity		
Runtime Estimates	Half Load (min)	11			12.2	10	
	Full Load (min)	4			4	3	
Physical	Dimension, D X W X H (mm)	288 x 145 x 223	400 x 145 x 238	425 x 190 x 336	374 x 190 x 685	447 x 190 x 685	
	Weight (kgs)	9.3	16.8	26.8	54	65	
Features	LED	✓			✓	✓	
	LCD	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators					
	EPO	-			✓	✓	
	USB Communication Port	✓			✓	✓	
	Intelligent Slot	Yes					
	DB-9 RS-232	Supports Windows 2000/2003/XP/Vista/2008/7/8/10					
	Input Breaker	✓			✓	✓	
	Battery User Disconnect	✓			✓	✓	
	Manual Maintenance Bypass	-			✓	✓	
ECO Mode	✓			✓	✓		
Protection	Surge Energy Rating (Joules)	600 J					
Environment	Humidity	0 to 95% relative humidity, noncondensing					
	Temperature	0° to 40°C at rated load			0° to 40°C at rated load		
	Noise Level	Less than 50dBA			Less than 55dB	Less than 58dB	
Conformance	Regulatory Approvals	CE					
	Warranty	2 years					

Life Is On

APC
by Schneider Electric

Technical Specifications

Easy UPS 1 Ph Online Standard Models (Rack Mount)

Model		SRV1KRI(RK)	SRV2KRI(RK)	SRV3KRI(RK)	SRV6KRI(RK)	SRV10KRI(RK)
Input	Nominal Input Voltage	230Vac				
	Input Connection	IEC C14	IEC C14	IEC C20	Terminal Block	
	Input Frequency	50 Hz / 60 Hz				
	Input Voltage Range (60% Load)	110 Vac – 285 Vac			110 Vac – 300 Vac ± 3%	
	Input Power Factor (100% Load)	≥ 0.95			≥ 0.99	
Output	Topology	Online				
	Output Power Capacity (Watts)	800 W	1600 W	2400 W	6000 W	10000 W
	Output Power Capacity (VA)	1000 VA	2000 VA	3000 VA	6000 VA	10000 VA
	Output Voltage	220/230/240VAC				
	Frequency (Battery Mode)	50/60Hz +/- 0.5%			50/60Hz +/- 0.1 Hz	
	Waveform Type	Pure Sinewave				
	Output Voltage Regulation	± 1%				
	Transfer Time (AC to DC)	Zero				
	Total Output Connections	IEC 3*C13	IEC 4*C13	IEC 6*C13+1*C19	Terminal Block	
	Efficiency (AC Mode)	88%			94%	
	Current Crest Ratio	3:1				
Battery	Battery Type	Maintenance-free sealed Lead-Acid battery				
	Typical Recharge Time	4 hours recover to 90% capacity			3 hours recover to 90% capacity	
Runtime Estimates	Half Load (min)	11	12	13	12.2	10
	Full Load (min)	4	4	4	4	3
Physical	Dimension, D X W X H (mm)	312x438x86 (2U)	462x438x86 (2U)	632x438x86 (2U)	UPS:612 x 438 x 88 (2U) BATT:710x 438 x 88 (2U)	UPS:612 x 438 x 88 (2U) BATT:710 x 438 x 88 (2U)
	Weight (kgs)	11	18.2	27.6	UPS:14	UPS:16.5
					BATT:46	BATT:53
Features	LED	✓			✓	✓
	LCD	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators				
	EPO	-			✓	✓
	USB Communication Port	✓			✓	✓
	DB-9 RS-232	Supports Windows 2000/2003/XP/Vista/2008/7/8/10				
	Input Breaker	✓			✓	✓
	Battery User Disconnect	✓			✓	✓
	ECO Mode	✓			✓	✓
Protection	Surge Energy Rating (Joules)	600 J				
Environment	Humidity	0 to 95% relative humidity, noncondensing				
	Temperature	0° to 40°C at rated load			0° to 40°C at rated load	
	Noise Level	Less than 50dBA			Less than 55dB	Less than 58dB
Conformance	Regulatory Approvals	CE				
	Warranty	2 years				

Life Is On

APC[®]
by Schneider Electric

Technical Specifications

Easy UPS 1 Ph Online Extended Runtime Models (Tower)

Model		SRV1KIL	SRV2KIL	SRV3KIL	SRV6KIL	SRV10KIL	
Input	Nominal Input Voltage	230Vac					
	Input Connection	IEC C14	IEC C14	IEC C20	Terminal Block		
	Input Frequency (V)	50Hz / 60 Hz					
	Input Voltage Range (60% Load)	110 Vac – 285 Vac			110 Vac – 300 Vac ± 3%		
	Input Power Factor (100% Load)	≥ 0.95			≥ 0.99		
Output	Topology	Online					
	Output Power Capacity (Watts)	800 W	1600 W	2400 W	6000 W	10000 W	
	Output Power Capacity (VA)	1000 VA	2000 VA	3000 VA	6000 VA	10000 VA	
	Output Voltage	220/230/240VAC					
	Frequency (Battery Mode)	50/60Hz +/- 0.5%			50/60Hz +/- 0.1 Hz		
	Waveform Type	Pure Sinewave					
	Output Voltage Regulation	± 1%					
	Transfer Time (AC to DC)	Zero					
	Total Output Connections	IEC C13*3	IEC C13*4	IEC C13*6 + IEC C19*1	Terminal Block		
	Efficiency (AC Mode)	88%			94%		
	Current Crest Ratio	3:1					
External Battery Pack	Charging Current	4A			1 to 4 A (adjustable)		
	Battery Type	Maintenance-free sealed Lead-Acid battery					
	Part Number	SRV36BP-9A	SRV72BP-9A	SRV72BP-9A	SRV240BP-9A	SRV240BP-9A	
Physical	Dimension, D X W X H (mm)	Power Module	288 x 145 x 223	400x 145 x 238	400x 145 x 238	374 x 190 x 336	447x 190 x 336
		Battery Pack	400 x 145 x 238	425 x 190 x 336	425 x 190 x 336	485 x 190 x 368	485 x 190 x 368
	Weight (kgs)	Power Module	4.4	7.1	7.8	13	16.5
		Battery Pack	19.6	38	38	60	60
Features	LED	✓	✓	✓	✓	✓	
	LCD	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators					
	EPO	-	-	-	✓	✓	
	USB communication port	✓	✓	✓	✓	✓	
	DB-9 RS-232	Supports Windows 2000/2003/XP/Vista/2008/7/8/10					
	Input Breaker	✓	✓	✓	✓	✓	
	Intelligent Slot	✓	✓	✓	✓	✓	
	Battery user disconnecter	✓	✓	✓	✓	✓	
	Manual Maintenance Bypass	-	-	-	✓	✓	
ECO Mode	✓	✓	✓	✓	✓		
Protection	Surge Energy Rating (Joules)	600 J					
Environment	Humidity	0 to 95% relative humidity, non-condensing					
	Temperature	0° to 40°C at rated load					
	Noise Level	Less than 50dB			Less than 55dB	Less than 58dB	
Conformance	Regulatory Approvals	CE					
	Warranty	2 Years					

Life Is On

APC
by Schneider Electric

Technical Specifications

Easy UPS 1 Ph Online Extended Runtime Models (Rack Mount)

Model		SRV1KRIL	SRV2KRIL	SRV3KRIL	SRV6KRIL	SRV10KRIL	
Input	Nominal Input Voltage	230Vac					
	Input Connection	IEC C14	IEC C14	IEC C20	Terminal Block		
	Input Frequency	50Hz / 60 Hz					
	Input Voltage Range (60% Load)	110 Vac – 285 Vac			110 Vac – 300 Vac ± 3%		
	Input Power Factor (100% Load)	≥ 0.95			≥ 0.99		
Output	Topology	Online					
	Output Power Capacity (Watts)	800 W	1600 W	2400 W	6000 W	10000 W	
	Output Power Capacity (VA)	1000 VA	2000 VA	3000 VA	6000 VA	10000 VA	
	Output Voltage	220 / 230 / 240VAC					
	Frequency (Battery Mode)	50/60Hz +/- 0.5%			50/60Hz +/- 0.1 Hz		
	Waveform Type	Pure Sinewave					
	Output Voltage Regulation	± 1%					
	Transfer Time (AC to DC)	Zero					
	Total Output Connections	IEC C13*4	IEC C13*4	IEC C13*6 + IEC C19*1	Terminal Block		
	Efficiency (AC Mode)	88%			94%		
	Current Crest Ratio	3:1					
External Battery Pack	Charging Current	4A			1 to 4 A (adjustable)		
	Battery Type	Maintenance-free sealed Lead-Acid battery					
	Part Number	SRV36RLBP-9A	SRV72RLBP-9A	SRV72RLBP-9A	SRV240RLBP-9A	SRV240RLBP-9A	
Physical	Dimension, D X W X H (mm)	Power Module	332 x 438 x 86	462 x 438 x 86		615 x 438 x 86.5 (2U)	615 x 438 x 86.5 (2U)
		Battery Pack	412 x 438 x 86	632 x 438 x 86		606 x 438 x 131 (3U)	606x 438 x 131 (3U)
	Weight (kgs)	Power Module	6	9.2	9.5	14	16
		Battery Pack	21	42.5		63	63
Features	LED	✓	✓	✓	✓	✓	
	LCD	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators					
	EPO	-	-	-	✓	✓	
	USB communication port	✓	✓	✓	✓	✓	
	DB-9 RS-232	Supports Windows 2000/2003/XP/Vista/2008/7/8/10					
	Input Breaker	✓	✓	✓	✓	✓	
	Intelligent Slot	✓	✓	✓	✓	✓	
	Battery user disconnecter	✓	✓	✓	✓	✓	
ECO Mode	✓	✓	✓	✓	✓		
Protection	Surge Energy Rating (Joules)	600J					
Environment	Humidity	0 to 95% relative humidity, non-condensing					
	Temperature	0° to 40°C at rated load					
	Noise Level	Less than 50dB			Less than 55dB	Less than 58dB	
Conformance	Regulatory Approvals	CE					
	Warranty	2 Years					

Life Is On

APCTM

by **Schneider** Electric

132 Fairgrounds Rd
West Kingston, RI 02892
Phone: + 01 (401) 789-5735
www.schneider-electric.com

©2019 Schneider Electric. All Rights Reserved. Schneider Electric | Life Is On, APC, and PowerChute are trademarks and the property of Schneider Electric SE, its subsidiaries, and affiliated companies. All other trademarks are the property of the respective owners.



APC Easy UPS On-Line SRV 1000VA 230V SRV1KI

- Includes: Basic UPS signalling RS-232 cable, CD with software, USB cable, User manual

Output	
Output power capacity	800 Watts / 1.0kVA
Max Configurable Power (Watts)	800 Watts / 1.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Efficiency at Full Load	88.0 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(3) IEC 60320 C13 (3) IEC 320 C13
Bypass	Internal bypass (automatic and manual)

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	IEC 60320 C14
Cord Length	1.5meters
Input voltage range for main operations	110 - 285 Adjustable (half load), 160 - 280V
Number of Power Cords	1
Efficiency at Full Load	88.0 %

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS On-Line SRV 1000VA 230V | SRV1KI | Downloaded on 12/08/2020 (EST)

Input	
Other Input Voltages	220, 240

Batteries & Runtime	
Battery type	Lead-acid battery
Included Battery Modules	1
Typical recharge time	4hour(s)
Battery Charge Power (Watts)	38 Watts
Battery Volt-Amp-Hour Capacity	216
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	DB-9 RS-232, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	600Joules

Physical	
Maximum Height	223MM, 22.3CM
Maximum Width	145MM, 14.5CM
Maximum Depth	288MM, 28.8CM
Net Weight	9.3KG
Shipping weight	10.6KG
Shipping Height	330MM, 33.0CM
Shipping Width	235MM, 23.5CM
Shipping Depth	365MM, 36.5CM
Color	Black

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3048meters
Storage Temperature	-20 - 50 °C
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	50.0dBA
Online thermal dissipation	372.0BTU/hr
Protection Class	IP20

Conformance	
Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 year (manufacturer's defect)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.